

SOIL CONSERVATION SERVICE
STANDARD AND SPECIFICATIONS
LAND RECLAMATION
SHAFT AND ADIT CLOSING (NO.)
STANDARD

Definition

Closing vertical and horizontal underground mine openings

Scope

This standard applies to abandoned mine shafts and adits to underground mines that are being treated as a part of surface reclamation. It also applies to sinkholes and pits caused by collapse of underground mines.

Purpose

To close mine shafts and adits to reduce subsidence problems, hazards to humans and animals, the emission of hazardous gases, and the pollution of surface or ground water; to protect other resources; to improve the environment; and to provide for beneficial land use.

Condition Where Practice Applies

To locations where vertical shafts, sinkholes, adits, and drift openings to underground mines have been left open. The practice would normally be associated with some type of surface treatment to reclaim the affected area

Planning Considerations

1. Mine depth, slope, and layout.
2. Geologic strata where the opening and mine are located.
3. Presence of additional openings to the same or adjacent mines
4. Land use, dwellings, roads, and other structures nearby.
5. Water level, quality, and flow rates, including water moving from connecting mines.
6. Associated surface subsidence.
7. Hazardous gases present or being released.
8. Potential for combustion.
9. Location and condition of proposed fill material

10. Topography.
11. Drainage patterns.

Design Criteria

Agricultural Engineering Note 1, January 1981, contains guidance on investigation, safety, design, and construction and is to be used as a procedural guide with this standard.

Designed filling. All debris and material not meeting backfill material specification should be removed, leaving the clean, solid material that existed prior to beginning of backfill operations. Material remaining should be compacted, if necessary.

Vertical shafts should be filled to about 5 feet from the surface with a properly designed filter consisting of nonacid-forming, free-draining materials. The remainder of the shaft should be filled with random fill materials interspersed with layers of clay, approximately 2 feet thick, or other impervious materials that would retard the passage of water or gas. The opening should be overfilled to allow for settling. Normally, this would be 10 percent of the depth of the shaft, or 5 feet, whichever is less. The surface should be rounded and vegetation established in accordance with appropriate SCS standards.

Sinkholes that are open, active, and/or passing a significant quantity of water require a properly designed filter of nonacid-forming, free-draining material. Sufficient soil covering shall be placed to sustain planned vegetation. Sinkholes that are closed, inactive, and not passing a significant quantity of water may require only backfilling with suitable soil material. The allowance made for settlement should be 10 percent of the fill depth, and the area should be overfilled accordingly. Investigation of the sinkhole is necessary to determine the method of filling.

Caps. Caps are constructed for reinforced concrete or steel beams and grates or solid steel plates. Bedrock must be at or near the ground surface if shafts are to be closed by caps. Caps must be designed and supported by the bedrock with sufficient bearing surface to prevent caving or burrowing into the shaft. The surface of the cap must be raised not less than 1 foot above the surrounding terrain to provide good visibility and positive drainage away from the cap installation. Caps must be designed as a two-way slab or beam with sufficient strength to support anticipated loads. The cap and fittings, access holes, and vent pipe should be reasonably vandal proof. Adits and drift openings should be sealed in a similar manner by walling up the entrance securely to the roof. Detailed structural and support design as required.

Plugs. Plugs are to be used only if no other practical solution is available. Installed at substantial distances below the ground surface, they are used where the shaft is to be filled to the surface (see "Designed filling"), but the shaft below is to remain open. Plugs should be made of properly designed reinforced concrete and placed in firm bedrock to ensure against failure.

Plugs are to be designed and located in the shaft where an adequate bond with the original bedrock can be obtained on the sides of the shaft, with sufficient strength to support the backfill to be placed. They can be

designed as watertight and gas-tight, but are often designed with small weep holes to allow free drainage. Filters may be needed to prevent soil from seeping out weep holes with water.

Barriers and dams. Barriers are built in adits to prevent humans and animals from entering the tunnel, and if near the bottom of a shaft, may be used to prevent lateral spreading of backfill material and to support filling of the shaft. Barriers are constructed of stones, crushed rock, quarry run rock, gravel, shale, or similar nonacid-forming, free-draining materials. The barrier is to be at least three tunnel diameters thick. If a concrete or masonry wall is not used to support the barrier, it should be three diameters thick at the top of the tunnel with at least a 3:1 side slope to the bottom. If barriers are to extend to the ground surface, the surface must be at least 4 feet of soil materials and established to vegetation in accordance with appropriate SCS standards. If needed, a permanent drainage system using pipe or rock toes should be installed through this covering. Traps to prevent air or gas passage may be necessary. Vents may be required to prevent build-up of gas which could release at undesirable locations.

Dams are constructed the same as barriers except they are designed to be essentially watertight and to withstand a known hydraulic head. They must be constructed of impermeable materials to be sealed.

Enclosures. Enclosures should be used only where it is essential to occasionally enter or gain access to shafts or adits for pumping or other reasons. Enclosures may be made of concrete, masonry, or "anti-intruder" chain link and barbed wire fences. Enclosures can be used only where periodic inspection and maintenance is ensured. In all cases, enclosures should be constructed to keep humans and animals out and should be located so that no subsidence or caving can break the integrity of the enclosure.

Safety precautions. When the presence of harmful amounts of gas is evidenced or suspected and work involves shafts or adits, tests are to be made to determine the presence of gas that could be harmful to humans, animals, the use of equipment, or that could cause a fire or an explosion.

If hazardous gas is present, ventilation and safety precautions are to be taken as necessary for the closing operation, and permanent ventilation measures are to be installed if needed. Only persons experienced and trained in this activity are to provide guidance on measures to be taken.

Extra precaution must be taken when searching for concealed shafts and adits. At least two persons should conduct a search, leaving their specific schedule with others. Extra care must be exercised when the ground is unstable or if gas may be present. Safety barriers, ropes, safety belts, gas detectors, and other equipment must be used as necessary during site reconnaissance, surveying, and foundation investigation and construction activities. A collapse zone should be established, clearly marked with fencing and warning notices, and no person should enter this zone without wearing a proper safety harness. Sturdy bumper blocks or other devices must be used to keep machinery and trucks from falling into shafts and subsidence pits. Whenever possible, bulldozer blades and other items should be larger than the hole being filled.

Maintenance

Maintenance activities must be outlined in the reclamation maintenance plan. Maintenance is essential because of the strong likelihood of additional subsidence, water drainage, failure of vegetation, and other problems associated with mine reclamation. Restrictive barriers, fences, and covers are to be maintained to accomplish their purpose. Regular periodic inspections must take place and prompt repair and follow-up be carried out.

Environmental

All disturbed areas shall be reshaped and regraded to blend with surrounding land features. Visual resources must be given the same consideration as other design features in planning, design, and installation. Exposed areas of earth shall be covered with soil materials and established with vegetation or protected by other means as soon as practicable. Access roads must be maintained and foot and vehicular traffic controlled to protect the work.

Plans and Specifications

Plans and specifications for closing mine shafts and adits shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose.